



## **UL SPECIFICATION**

- \* FIXTURE SHALL BE LISTED FOR LOCATION ONLY AND LABELED AS SUCH.
- \* FIXTURE MUST BE MANUFACTURED IN ACCORDANCE WITH UL STANDARD 1598.

## PARTS SPECIFICATIONS ITEM QTY DESCRIPTION

- A (1) SOCKET- UL LISTED/CSA CERTIFIED
  BASE= MEDIUM
  SOCKET= PORCELIN
  SEE LEAD WIRE FOR SOCKET WIRE SPEC.
- B (1) LEAD WIRE- 120" FROM FRAME TOP UL LISTED/CSA CERTIFIED, AWG #18 105°C SPT-1 BLACK WIRE.
  STRIP 1/2 [12.7], SPLIT 3 [76.2].
  FROM TOP OF SCROLL.
  (SEE CHART FOR COLOR).
- C (1) GROUND WIRE- 120" FROM FRAME TOP 1/4 LAY COPPER GROUND WIRE. FROM TOP OF SCROLL. (SEE CHART FOR TINT).

INNOVATIONS LIGHTING

DESIGN COPYRIGHT - 29/07/2020

ALL RIGHTS RESERVED AND MAY

NOT BE DUPLICATED WITHOUT OUR

WRITTEN PERMISSION

NO. PART NO. DESCRIPTION REQ.

OTICE: ANY DESIGN OR OTHER INFORMATION HEREON DEVELOPED BY THIS COMPANY CONFIDENTIAL MATERIAL AND EXCLUSIVE PROPERTY OF THE L.D. ALIYA CO. DISCLOSURE REPRODUCTION REQUIRES THE WRITTEN CONSENT OF THE L.D. ALIYA CO.



DRAWN IN	"mm" DIMENSION INDICATED IN [] DIMENSION IN [] IS FOR REF. ONLY						
THIRD ANGLE	TOLLIVANOLS (LACEFT AS NOTED)						
PROJECTION	DECIMAL	ANGULAR	FRACTIONAL ± 1/32		SCALE		
	NONE ±.031 .X ±.015 .XX ±.010 .XXX ±.005	± 1/2°			1:7		
		DATE	DRAWN BY	CHECKED BY		APPROVED BY	
		3/31/2021			X	X	



PART NO. PENDANT	REV.
TEM NO. 341-5CR-BK	REV.