

UD501KOG5

LG PuriCare™ 50* Pint Dehumidifier

ENERGY STAR® Qualified
 Dehumidification (Pts/Day) 50*
 Convenient To Use Water Bucket & Ergonomic Handle
 Designed With Safety In Mind
 Full Bucket Indicator with Auto Shut-Off
 Washable Filter

* Pint Removal Performance Operating Conditions
 Under the DOE test standards before June, 13th in 2019 (DOE Test Procedure 10 CFR Part 430, subpart B, appendix X) the pint removal performance was at 80°F.
 After June, 13th in 2019 the DOE test standard (DOE Test Procedure 10 CFR Part 430 subpart B, appendix X 1) changed to 65° F



LG PuriCare™
 Dehumidifier



CAPACITY	
Dehumidification (pts/day)	50.0
Power Rating	115V / 60Hz
Watts	545.0
Amps	5.0
IEF	1.80
Circuit Size (Amps)	10
Compressor Type	Rotary
Refrigerant Type	R 410
Refrigerant Weight (oz)	6.00
Refrigerant Weight (g)	170
Noise Level (High / Low) @ Average	50/48
FEATURES	
LED Display (Set Humidity)	Yes
Touch Pad Button	Yes
Energy Timer	Yes
Auto Restart	Yes
Safety Standby	Yes
Automatic Humidistat Control	Yes
Fan Speed Selection Switch	Touch Pad Button
Fan Speed	2
CMM (H/L)	5.5 / 4.5
CFM (H/L)	194.2 / 158.9
Fan Type	Turbo
Bucket Type	Removable
Bucket Loading Direction	Side
Bucket Full Indicator Lamp	Yes
Bucket Pints	13.3

Automatic Shut-Off System	Yes
Automatic Defrost Control	Yes
Low Temperature Operation (*F)	41
External Drain Connector	Yes
Washable Air Filter	Yes
APPEARANCE	
Color	Black
Easy-Roll Casters	Yes
DIMENSIONS & WEIGHTS	
Overall Width mm(inches)	427(16.8)
Height	665(26.2)
Depth	321(12.6)
Packing Width mm(inches)	482(19.0)
Height	732(28.8)
Depth	365(14.3)
Approximate Shipping Weight (lbs)	49.2
Approximate Shipping Weight (kg)	22.3
Approximate Net Weight (lbs)	43.9
Approximate Net Weight (kg)	19.9
STUFFING QUANTITY	
40Ft High	426
40Ft	426
20Ft	198
UPC	
UD501KOG5	048231601009