

SPEAKMAN® SM-3470

Versatile™ Pressure Balance Handicap Shower/Tub Package

FEATURES:

- Versatile shower system includes Sentinel Mark II® concealed anti-scald balanced pressure valve with integral diverter and integral stops and hand held spray combination.
- Chrome plated brass wall plate with metal index.
- Chrome plated brass lever handle.
- Independent center sleeve allows up to 1 in. of rough-in variation.
- Adjustable temperature limit stop. Brass body.
- Pressure balancing and ceramic temperature regulating cartridge with built-in check valves.
- Can be installed back-to-back. Roughing-in template.
- Four port valve with 1/2 in. female copper sweat inlets and shower outlet (Tub outlet 1/2 NPT female).
- Transfer valve with chrome plated metal lever handle and brass body.
- Chrome plated brass supply ell with wall flange.
- 69 in. square lock stainless steel hose with rubber liner.
- Swivel connector. In-line vacuum breaker.
- S-1554 tub spout.
- VS-100-PC handshower with flow control device reduces flow to 2.5 gpm (9.46 L/min) maximum
- S-2272-E2 showerhead with 2.0 gpm (7.57 L/min) flow rate.
- S-2500 shower arm and wall flange.
- Two wall-mounted posts. Swivel connector.



FINISH:



PC

COMPLIANCE:

- Meets ASSE 1016 & ASME 112.18.1/CSA B125.1 standards (SM-3400 valve)
- WaterSense certified (S-2272-E2 shower head)

OPTIONS: Add suffix to model

- Less showerhead -LH
- 69 in. white vinyl hose -VH
- S-2251 showerhead -1
- S-2252 showerhead -2
- S-2253 showerhead -3
- S-2292 showerhead -9
- Contractor Packs Available

WARRANTY:

- 5 year limited

Architect/Engineer Approval Space:

SPEAKMAN
400 ANCHOR MILL ROAD
NEW CASTLE, DE 19720

P: 800-537-2107
F: 800-977-2747
W: WWW.SPEAKMAN.COM
R: OCTOBER 2017

NOTE: 1. All dimensions are in inches (millimeters) unless otherwise specified and are subject to change without notice. 2. Unless otherwise specified all inlets and outlets are 1/2" female copper sweat. 3. The location of the wall posts(2) and supply ell are optional, but restricted by the 69" hose length running from the supply ell connection to hand shower and the 6" minimum requirement between the in-line vacuum breaker and top of hand shower (hand shower adjusted to the highest position). 4. For ADA mounting locations consult ADAAG, ANSI A117.1 or state regulations.

DIMENSIONS:

